



Desktop Retransfer Dual-sided Card Printer

R330



SEAOXY R

Key Features

- With dye-sublimation retransfer printing technology
- Higher image quality and clear text, realizing professional-level printing effects
- Perfectly realize the ultra-edge printing
- High printing speed engine
- All-metal internal structure, more stable continuous printing ability
- Support PVC, composite PVC, ABS, PET, PC
- Standard dual-sided printing module, standard flattening module
- With a 3.5-inch color touch-screen, the operation is more intuitive and convenient

Multi-function optional modules

- Dual interface card encoding module
- UHF chip card encoding module
- Contactless ID card encoding module
- Magnetic stripe card encoding module
- Electronic lock/mechanical lock of input hopper
- Electronic lock/mechanical lock of defective card slot
- Electronic lock/mechanical lock of ribbon door
- Lamination module

Consumables

- Monochrome black ribbon: 100x60mm
- Full panel YMCK ribbon: 500 prints/roll and 1000 prints/roll
- Full panel YMCKK ribbon: 500 prints/roll
- Full panel YMCKI ribbon: 500 prints/roll
- Full panel YMCKHs ribbon: 500 prints/roll
- Security YMCFK ribbon: 500 prints/roll
- Transparent retransfer film: 500 prints/roll and 1000 prints/roll

Value-added functions

- Alarm for no card, defective card slot
- Manual feeding card on back end and recycling pending card
- Available to set the card-out direction



Dye-sublimation retransfer printing technology



Professional printing software come with the printer

Specifications

Product Name	R330/Desktop Retransfer Dual-sided Card Printer
Printer Dimension	568mm × 272mm × 398mm (Length x Width x Height), 12Kg
Power	AC100~240V, 50/60Hz, 24V \equiv 15A 360W
Print Speed	Monochrome black printing: 12-16s per card (single-sided), 27-30s per card (dual-sided), use ribbon saving technology Full-color YMCK Printing: 20s per card (single-sided), 38s per card (dual-sided)
Print Dimension	ISO CR80 (53.98mm×85.60mm) ultra-edge printing
Print Resolution	300dpi × 300dpi
Print Method	Dye sublimation retransfer printing
Memory	256MB
Interfaces	Standard USB2.0 & Ethernet, WIFI (optional)
Card Material	PVC, composite PVC, ABS, PET, PC
Card Thickness	0.3-1.05mm (hopper adjustment required)
Input hopper capacity	200pcs (0.76mm)
Output hopper capacity	200pcs (0.76mm)
Defective card slot capacity	25pcs (0.76mm)
Buzzer	Yes
Indicator	Red/Green indicator
LCM Display	3.5 inch color touch-screen
Software	Driver: Support Windows XP/7/8/10/11, Windows Server 2003/2008/2012/2016, Linux, Mac OS, and NeoKylin, Kylin, UOS and other made-in-China operating system. Development Kit: Support Windows XP/7/8/10/11, Windows Server 2003/2008/2012/2016, Linux, and NeoKylin, Kylin, UOS and other made-in-China Operating System Card Design Software: iCARDE card design software, support Windows XP/7/8/10 operating systems
Warranty	Card printer: 3 years (artificial damage excluded) Print head: lifetime warranty
Operation Environment	Regular running temp: 15°C-30°C (59-86°F), 20%-65% RH non-condensing Lowest/Highest running temp: 0°C (32°F)/40°C (104°F), 20% to 65% RH non-condensing.
Storage Environment	Temp.: -5°C-70°C (23-158°F), 20% to 70% RH non-condensing and ventilation environment

